



CL-SW10G-2404

20-Port GbE (100M/1G)SFP + 4 TP/(100/1G) SFP Combo + 4-Port 1G/10G SFP+ L2 Plus Carrier Ethernet Switch



Key Features

- L2+ features provide better manageability, security, QoS, and performance
- IEEE 802.3ah MAC Layer OAM and IEEE802.1ag Ethernet CFM
- ITU-T Y.1731 Ethernet OAM Performance monitoring
- 802.3az Energy Efficient Ethernet standard
- MEF E-tree service over MPLS (includes E-LINE, E-LAN and E-TREE(EP-TREE, EVP-TREE)),available at FW v1.20
- IPv6 and s-Flow supports
- ITU-T G.8031 Ethernet Linear Protection and ITU-T G.8032 Ethernet Ring Protection Switching
- Sync-Ethernet and IEEE1588v2 PTP for Carrier Ethernet management requirement
- AC(100~240VAC) and DC(-48VDC) dual power input for power redundancy requirement
- QinQ support

Overview

The SW10G-2404, the next generation L2+ Carrier Ethernet Access Fiber switches from Carelink, is a 20-port GbE SFP, 4-port Combo GbE (RJ-45/SFP) and 4-port 10GbE (SFP+) Ethernet L2+ Carrier Ethernet Switch portfolio of affordable carrier switches and a standard switch that meets all IEEE 802.3/u/x/z/ab/ae standards. It provides the ideal combination of affordability and capabilities for Carrier Access networking includes IEEE802.3ah MAC Layer OAM, IEEE802.1ag Ethernet CFM, ITU-T Y.1731 Ethernet OAM Performance Monitoring, ITU-T G.8031 Ethernet Linear Protection, ITU-T G.8032 Ethernet Ring Protection Switching, Sync-Ethernet and IEEE1588v2 PTP for Carrier Ethernet management requirement. It is suitable for Carrier Ethernet applications and helps you create a more efficient, better-connected workforce. This switch can be managed through RS-232 serial port, or through Ethernet port using CLI or Web-based management. With the SNMP agent, the network administrator can manage the switch, configure and control in a friendly way. It supports AC and DC Dual Power input (100~240VAC/-48VDC) for Power Redundancy requirement.



CL-SW10G-2404

20-Port GbE (100M/1G)SFP + 4 TP/(100/1G) SFP Combo + 4-Port 1G/10G SFP+ L2 Plus Carrier Ethernet Switch

Applications

Whether you want to create a high-performance carrier Access network to connect all clients' computers or an application to deliver data, voice, and video services, the SW10G-2404 switch provides a solution to fit your requirements. Possible carrier Ethernet implement scenarios include:

- **IEEE 802.3ah Ethernet OAM, IEEE 802.1ag Ethernet CFM and ITU-T Y.1731 Performance Monitoring:** The SW10G-2404 switch provides the OAM features: simple link-level information, track end-to-end connectivity across the network and performance statistics. Simple link fault management (LFM) for Ethernet links is defined in IEEE 802.3ah. IEEE 802.1ag Ethernet CFM(Connectivity Fault Management) provides Fault monitoring using the continuity check protocol, Path discovery and fault verification using the link trace protocol and fault isolation using the loopback protocol. ITU-T Y.1731 allows network administrator to monitor frame delay, frame delay variation, frame loss and availability between two nodes of the network.
- **ITU-T G.8032:** The SW10G-2404 switch supports ITU-T G.8032 which defines the multi-node ring protection architecture for native Ethernet networks. This is important as carriers want to move away from SONET/SDH to a native Ethernet based infrastructure.
- **Sync-Ethernet and IEEE1588v2 PTP:** The SW10G-2404 switch supports comprehensive IEEE 1588v2 and Synchronous Ethernet emulation. Both IEEE 1588v2 and ITU-T Sync-E Ethernet synchronization protocols, and can emulate link OAM and service OAM protocols. The IEEE 1588v2 PTP standard addresses frequency, phase, and time-of-day synchronization requirements, making it ideal for applications such as LTE TDD.
- **Unified communications with open standards:** To be a managed network solution, it provides the high performance and advanced networking quality to deliver all networking communications and data (such as IP telephony, IP surveillance, and Video Streaming) over a single network.
- **Advanced network security:** The SW10G-2404 switch provides enhanced and advanced network security to guests in public or private area, such as a hotel, an office lobby, or any area open to guests. Using powerful but simple to install security and traffic separating abilities, through guest VLAN or guest access control technology, it will help you to isolate vital networking traffic from guest services and keep guests' network sessions private from each other.



CL-SW10G-2404

20-Port GbE (100M/1G)SFP + 4 TP/(100/1G) SFP Combo + 4-Port 1G/10G SFP+ L2 Plus Carrier Ethernet Switch

Product Specifications

Feature	Description		
Performance			
Switching capacity and forwarding rate	Model Name	Capacity in Millions of Packets per Second (mpps) (64-byte packets)	Switching Capacity in Gigabits per Second (Gbps)
	SW10G-2404	95.23	128
Layer 2 Switching			
Spanning Tree Protocol (STP)	Standard Spanning Tree 802.1d Rapid Spanning Tree (RSTP) 802.1w Multiple Spanning Tree (MSTP) 802.1s		
Trunking	Link Aggregation Control Protocol (LACP) IEEE 802.3ad ●Up to 14 groups ●Up to 8 ports per group		
VLAN	Supports up to 4K VLANs simultaneously (out of 4096 VLAN IDs) ● Port-based VLAN ● 802.1Q tag-based VLAN ● MAC-based VLAN ● Management VLAN ● Private VLAN Edge (PVE)		
Voice VLAN	Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS		
Generic VLAN Registration (GVRP)	Protocols for automatically propagating and configuring VLANs in a bridged domain		
DHCP Snooping	DHCP snooping provides security by filtering un-trusted DHCP messages and by building and maintaining a DHCP snooping binding table.		
IGMP v1/v2/v3 snooping	IGMP limits bandwidth-intensive multicast traffic to only the requesters		
IGMP Proxy	Support IGMP Proxy		
MLD v1/v2 snooping	Deliver IPv6 multicast packets only to the required receivers		
Security			
Secure Shell (SSH) Protocol	SSH secures Telnet traffic in or out of the switch, SSH v1 and v2 are supported		
Secure Sockets Layer (SSL)	SSL encrypts the http traffic, allowing advanced secure access to the browser-based management GUI in the switch		
IEEE 802.1X	IEEE802.1X: RADIUS authentication, authorization and accounting, MD5 hash, guest VLAN , single/multiple host mode and single/multiple sessions Supports IGMP-RADIUS based 802.1X Dynamic VLAN assignment		



CL-SW10G-2404

20-Port GbE (100M/1G)SFP + 4 TP/(100/1G) SFP Combo + 4-Port 1G/10G SFP+ L2 Plus Carrier Ethernet Switch

Layer 2 isolation Private VLAN Edge (PVE)	PVE (also known as protected ports) provides L2 isolation between clients in the same VLAN, supports multiple uplinks
Port Security	Locks MAC Addresses to ports, and limits the number of learned MAC addresses
IP Source Guard	Prevents illegal IP address from accessing to specific port in the switch
RADIUS/TACACS+	Supports RADIUS and TACACS+ authentication. Switch as a client
ARP Inspection	ARP inspection is a security feature that validates ARP packets in a network. ARP inspection determines the validity of packets by performing stored in a trusted database
Storm control	Prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on a port
ACLs	Supports up to 256 entries Drop or rate limitation based on source and destination MAC, VLAN ID or IP address, protocol, port, differentiated services code point (DSCP) / IP precedence, TCP/ UDP source and destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP) packets, IGMP packets, TCP flag
Quality of Service	
Hardware Priority Queue	Support 8 hardware queues
Scheduling	Strict priority and weighted round-robin (WRR) Queue assignment based on DSCP and class of service (802.1p/ CoS)
Classification	Port based; 802.1p VLAN priority based; IPv4/IPv6 precedence/ type of service (ToS) / DSCP based; Differentiated Services (DiffServ); classification and re-marking ACLs, trusted QoS
Rate Limiting	Ingress policer; egress shaping and rate control; per VLAN, per port and flow based
IPv6 applications	Web/ SSL, Telnet/ SSH, ping, Simple Network Time Protocol (SNTP), Trivial File Transfer Protocol (TFTP), SNMP, RADIUS, Syslog, DNS Client, protocol-based VLANs
Management	
Web GUI interface	Built-in switch configuration utility for browser-based device configuration (HTTP/ HTTPS). Supports configuration, system dashboard, maintenance, and monitoring
Dual Image	Dual image provides independent primary and secondary OS files for backup while upgrading
SNMP	SNMP version 1, 2c and 3 with support for traps, and SNMP version 3 user-based security model (USM)
Remote Monitoring (RMON)	Embedded RMON software agent supports RMON groups 1,2,3,9 (history, statistics, alarms, and events) for enhanced traffic management, monitoring and analysis
IPv4 and IPv6 dual stack	Coexistence of both protocol stacks to migration
Firmware upgrade	<ul style="list-style-type: none"> ➤ Web browser upgrade (HTTP/ HTTPS) and TFTP ➤ Upgrade through console port as well ➤ iCMS to deploy the switch firmware
Port mirroring	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe. Up to N-1(N is Switch's Ports) ports can be mirrored to single destination port. A single session is supported.



CL-SW10G-2404

20-Port GbE (100M/1G)SFP + 4 TP/(100/1G) SFP Combo + 4-Port 1G/10G SFP+ L2 Plus Carrier Ethernet Switch

Other management	HTTP/HTTPS; SSH; RADIUS; DHCP Client/ DHCPv6 Client ; SNMP; cable diagnostics; ping; syslog; Telnet client (SSH secure support)					
s-Flow	The industry standard technology for monitoring high speed switched networks. It is enabling performance optimization, accounting/billing for usage, defense against security threats.					
Green Ethernet						
Energy Detect	Compliant IEEE802.3az Energy Efficient Ethernet Task Force. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or Idle of client. Active mode is resumed without loss of any packets when the switch detects the link up					
Cable length detection	Adjusts the signal strength based on the cable length. Reduces the power consumption for cables shorter.					
General						
Jumbo frames	Frame sizes up to 9KB supported on Gigabit interfaces					
MAC Table	Up to 8K MAC addresses					
Discovery						
Link Layer Discovery Protocol (LLDP) (IEEE802.1AB) with LLDP-MED extensions	Used by network devices for advertising their identity, capabilities, and neighbors on a IEEE 802 local area network, principally wired Ethernet.					
Carrier Ethernet Protocol and features						
IEEE 802.3ah Ethernet OAM	Simple link fault management (LFM) for Ethernet links is defined in IEEE 802.3ah					
IEEE 802.1ag Ethernet CFM	IEEE 802.1ag Ethernet CFM function that provides connectivity fault management.					
Syn-E and IEEE1588v2	Both IEEE 1588v2 and ITU-T Sync-E Ethernet synchronization protocols, and can emulate link OAM and service OAM protocols.					
ITU-T Y.1731	ITU-T service OAM standard Y.1731 divides a network into maintenance domains in the form of hierarchy levels. (It will be released at FW v1.20)					
ITU-T G.8032	G.8032 provides the standards-based method of delivering high-performance Carrier Ethernet services over a multi-node ring protection switching. This is important as carriers want to move away from SONET/SDH to a native Ethernet based infrastructure.					
Interface						
Ports	Model Name	Total System Ports	100/1G SFP	UTP/(100/1G) SFP Combo	(1G/10G) SFP+	RJ-45 Port Out-of-band Management
	SW10G-2404	28	20	4	4	1
Environmental (preliminary)						
Dimensions	442(W)x 44(H) x 211.2(D) mm					
Weight (kg)	3.1 Kg					
Power	100-240 VAC 50~60 Hz, internal , universal, -48VDC Dual Power input					
Certification	CE Mark, FCC Part 15 Class A					
Operating temperature	0°C to 40 °C					



CL-SW10G-2404

20-Port GbE (100M/1G)SFP + 4 TP/(100/1G) SFP Combo + 4-Port 1G/10G SFP+ L2 Plus Carrier Ethernet Switch

Storage temperature	-20°C to70 °C
Operating humidity	10% to 90% , relative, non condensing

Package Contents

- Switch
- Power Cord
- Mounting Kit
- Console Cable
- CD-ROM with user manual documentation (PDF) included
- QIG (Quick Install Guide)

Minimum Requirements

- Web browser: Mozilla Firefox version 2.5 or later, Microsoft Internet Explorer version 6 or later
- Category 5 Ethernet network cable
- TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in network