



IW-2535DN 3.5" Digital TFT LCD Monitor

- High Quality 3.5" TFT LCD Panel.
- Wearable Punch for Hands-Free Operation.
- Dual Power Sources – Battery or DC Adapter.
- Brightness Adjustment .
- CE/FCC Approved. Comply with ROHS.
- No More Hand Phone Call Charges, Weak Walkie-talkie Signal or Need Second Person to Assist Positioning and Trouble Shooting Camera.

SPECIFICATIONS:

Screen Size	3.5 inch Digital TFT LCD
Resolution	480 (W) X 234 (H) mm dots
Contrast Ratio	350:1
View Angle	Horizontal 60 degrees (Typ.) / Vertical 55 degrees (Typ.)
Color Structure	R.G.B. STRIPE
Backlight	2 Groups LED
Video Signal	NTSC/PAL auto-switch
Input Signal	1.0Vp-p 75Ohm
Power	AA Battery X 8pcs or DC12V Adaptor
Power Consumption	8W max.
Brightness	200 cd/m2 minimum ; 250cd/m2 Typ. (Center of Display)
Response Time	Typ. 15ms; Max. 30 ms
OSD Function	Brightness / Contrast / Color / Tint / Rest Adjustable
Operation temperature	-10°C - 60 °C
Case Material	ABS HB
Storage temperature	-20°C - 70°C
Outlook Size & Weight	93(L) X 93 (W) X 23(D)mm / 550g with accessories and package
Accessories	Armful Bag / BNC with Cable / Power Cable / Battery Case
Accessories (Option)	2600mA NI-MH AA Battery x 8PCS + Battery Charger. (* Last for 6 hours continuously.)