



High-Power Ceiling Mount Wireless 300N PoE Access Point

300 Mbps, 2T2R MIMO, PoE Support, Bridge, Repeater, Multiple SSIDs and VLANs, 26 dBm, 400 mW

Part No.: **525251**

Wireless networking with three times the speed and five times the flexibility.

The Intellinet Network Solutions High-Power Ceiling Mount Wireless 300N PoE Access Point is the latest in wireless networking. Taking advantage of new technology, a wireless network can now see greatly enhanced network speeds.

Multiple Solutions in One Device

The Intellinet Network Solutions High-Power Ceiling Mount Wireless 300N PoE Access Point serves multiple purposes — an access point for your wireless network supporting multiple SSIDs and tagged VLANs, and a wireless bridge for point-to-point connections or WDS setups — and brings it all together so that the devices can access a high-speed Internet connection.

Flexibility

This access point can be configured in any one of five modes: 1) Access Point (AP), 2) Point-to-Point (PtP), 3) Point-to-Multi-Point (PtMP), 4) Universal Repeater or 5) AP Client (Station Infrastructure). Add support for multiple ESSIDs and VLANs to that and it becomes clear that whatever your requirements are the 300N Access Point provides the solution.

Power over Ethernet Port

The High-Power Ceiling Mount Wireless 300N PoE Access Point comes with a PoE PD port. This port can be used to power the device from a PoE-compliant LAN switch, which is very convenient in situations where AC power is not readily available.

Features:

- Up to 300 Mbps network link speed
- Super long-range indoor Wireless N range extender and universal repeater
- Smoke detector design
- Complies with 2.4 GHz IEEE 802.11n standard and is backward compatible with IEEE 802.11g/b standards

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- 2T2R MIMO technology for enhanced throughput and coverage
- Supports WMM function to meet the multimedia data bandwidth requirement
- Supports Wi-Fi Protected Setup (WPS)
- Supports WEP and WPA/WPA2 (TKIP and AES) data encryption
- IEEE 802.3af-compliant PoE-powered device with one PoE (PD) port
- DHCP server assigns IP addresses for all LAN users
- Supported modes: Access Point, Bridge Point-to-Point, Bridge Point-to-Multi-Point, WDS and Universal Repeater
- Supports multiple ESSIDs with individual security settings
- Multiple ESSIDs support VLAN tagging
- Easy installation through Web-based user interface
- Firmware upgradeable
- Use INTELLINET NETWORK SOLUTIONS Wireless N adapters for the best compatibility and performance
- Three-Year Warranty

Specifications:

Standards

- IEEE 802.1d (Spanning Tree Protocol)
- IEEE 802.11b (11 Mbps Wireless LAN)
- IEEE 802.11g (54 Mbps Wireless LAN)
- IEEE 802.11n (300 Mbps Wireless LAN)
- IEEE 802.1x (Network Access Control)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

General

- LAN port: 1 RJ45 10/100 Mbps data and power input port (PD port)
- LAN ports with Auto MDI/MDI-X
- Flash: 2 MB
- Memory: 16 MB SDRAM
- Chipset: Realtek RTL8196C + RTL8192CE
- Certifications: FCC Class B, CE Mark, RoHS

Wireless

- Wireless frequency range: 2.400 – 2.483 GHz
- Modulation technologies:
 - 802.11b: Direct Sequence Spread Spectrum (DSSS): DBPSK, DQPSK, CCK
 - 802.11g: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
 - 802.11n: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
- Data rates:
 - IEEE 802.11b (11 Mbps, 5.5 Mbps, 2 Mbps, 1 Mbps)
 - IEEE 802.11g (54 Mbps, 48 Mbps, 36 Mbps, 24 Mbps, 18 Mbps, 12 Mbps, 9 Mbps, 6

Mbps)

- IEEE 802.11n (MCS0-15: up to 300 Mbps)
- Output power:
 - OFDM: 23 dBm +/- 1.5 dBm (300 Mbps, 200 mW max.)
 - OFDM: 24 dBm +/- 1.5 dBm (250 Mbps, 40 mW max.)
 - CCK: 26 dBm +/- 1 dBm (11 Mbps, 400 mW max.)
 - Up to 20 dBm (100 mW in European Union)
- Wireless operation modes:
 - Access Point
 - Station Infrastructure (AP Client)
 - Point-to-Point Bridge
 - Point-to-Multi-Point Bridge
 - WDS Bridge
 - Universal Repeater
- Wireless security:
 - WEP encryption (64/128 bit)
 - WPA TKIP
 - WPA2 AES
 - WPA2 mixed
 - WPA RADIUS
 - 802.1x Authentication
 - Client access control through media access control (MAC) filter
- Antennas:
 - 2 Planar Inverted-F antennas PIFA with 3 dBi gain each
 - 2T2R MIMO mode (2 transmitters, 2 receivers)

LEDs

- Power
- WLAN Link/Act
- LAN Link/Act

Environmental

- Dimensions: 160 (W) x 127 (L) x 35 (H) mm (6.3 x 5.0 x 1.4 in.)
- Weight: 0.8 kg (1.7 lbs.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -20 – 60°C (4 – 149°F)

Power

- External power adapter: 5 V DC, 2.0 A
- Power consumption: 4 Watts max.
- Via PoE PD port: 48 V, 0.2 A

Package Contents

- High-Power Ceiling Mount Wireless 300N PoE Access Point
- User Manual
- Power adapter

