



PIH 252 / 254

Camera Series
Dome Camera

Metal Mini Dome Camera



Features

- Attractive Silver-Toned Finish
- Sturdy Metal Housing for Maximum Camera Protection
- Easy Lens Angle Adjustment
- Special Circuit to Avoid Color Rolling



Dimensions Dome:Φ62.5, Holder:Φ98mm

(Unit:mm)



Dome Camera

Name		Metal Mini Dome Camera				
Series Number		PIH-252/254				
Type		Standard Resolution		Super High Resolution		
Model	NTSC	PIH-2522N6	PIH-2522N3.6	PIH-2542N6	PIH-2542N3.6	
	PAL	PIH-2522P6	PIH-2522P3.6	PIH-2542P6	PIH-2542P3.6	
Lens	Focal Length	6.0 mm	3.6 mm	6.0 mm	3.6 mm	
	Iris	F1.8	F2.0	F1.8	F2.0	
	Angle of View	H	44.5°	73°	44.5°	73°
		V	33.1°	54.5°	33.1°	54.5°
D		56°	92°	56°	92°	
Power Supply		DC12V±10%				
Image Pick-up Device		Sony 1/3" Super HAD CCD Sensor				
Effective Pixels	NTSC	510 (H) x 492 (V)		768 (H) x 494 (V)		
	PAL	500 (H) x 582 (V)		752 (H) x 582 (V)		
Chip size		5.59mm(H) x 4.68mm(V)				
H/V Sync. Frequency	NTSC	15.734KHz / 59.94Hz				
		PAL 15.625KHz / 50Hz				
Scanning System		2:1 Interlace				
Sync. Mode		Internal				
Resolution		420 TV Lines		540TV Lines		
Min. Illumination		0.2 Lux / F1.8		0.5 Lux / F1.8		
S/N Ratio		More than 50dB (AGC Off)				
Auto Gain Control		36dB Variable Gain				
White Balance		ATW				
Aperture Gain Correction		Horizontal , Vertical				
Electronic Shutter		1/60 (1/50) S ~ 1/100,000S (Auto)				
Back Light Compensation		Auto				
Video Output		CVBS 1.0Vp-p / 75Ω BNC				
Gamma Characteristic		γ=0.45				
Power Consumption		2.2W				
Operating Temperature		-10°C ~ + 50°C (14°F ~122°F)				
Dimension		Dome:Φ62.5, Holder:Φ98				
Weight		230g				