



Model No.	QH-KB1010
OPERATION	
On Screen Display	English
LCD	Display command menu, protocol, current camera ID, output display ID and joystick status
Max Dome Connection	Available to connect with 32pcs High Speed Dome
Protocol	Built-in multi-protocol such as Pelco_P, Pelco_D, VIDO_B02, Pelco matrix and so on; Baud rate can be selected
Electrify	Auto-test the baud rate, protocol and object dome and object monitor
Dome Lens Control	Zoom, Focus and Iris Control
Dome Function Operation	Preset/Scan/Pattern/Tour Setup
Communication Interface	RS485, RS422, RJ45
RS485/RS422	DVR, PTZ Dome
RJ45	Matrix Connection
Matrix	Support PELCO Matrix
Keyboards Linkage	Max 4Pcs QH-KB1010
Communication Frequency	2400, 4800, 9600, 19200 Bps
Communication Distance	1.2km (RS485 and RS422 can achieve it)
Baud Rate	2400 Rate
MECHANICAL	
Joystick	Three Axis
Joystick Operation	control speed of pan/ tilt and zoom in/out; Two axis joystick can control speed of pan/ tilt

Color	Black
Material	Plastic
Dimensions	218*180*55mm
Net Weight	0.32Kg
ENVIRONMENTAL	
Operation Temperature	-0°C - 50°C
Storage Temperature	-20°C - 50°C
ELECTRICAL	
Input Voltage/Current	9V-12VAC/DC
Adapter Requirement	DC12V1.5A