



## SEEnergy SJT-02 Video Surveillance Joystick



# Technical Specification

## Physical

Power supply: 9V-12V DC

Power consumption: 5W Humidity: 0 ~ 95% (non condensing)

Dimension: 144mm\*184mm\*108mm

Net weight: 700g Gross weight: 1000g

Temperature: -10 °C ~ +50 °C

Humidity: 0 ~ 95% (Non-condensation)

Type of interface: USB

## Surveillance Software

Pi-Vu Central Basic +

Pi-Vu Central Basic

Pi-Vu Pro

Pi-Vu Pro Lite

- The SEEnergy SJT-02 has a three-axis joystick and USB interface. It integrates with SEEnergy video surveillance software platform. You just connect the joystick to the USB port on your computer and control the PTZ cameras.

## Features

- 3 axis PTZ joystick
- USB connector special for IP camera
- One time setting, Setting map can save in your computer (advise use the same interface and computer)
- Choice of button configurations
- Back side cable connector avoid cable plugged out
- 1.5 Meter cable line
- Bottom rubber avoid sliding during operation on the table

SEEnergy Corp. 4F, No.61, Dongsing RD., Taipei, 110, Taiwan, R.O.C. Tel: 886-2-8768-1518 Fax: 886-2-8787-8560 Email: sales@seenergy.com.tw Web: www.seenergy.com.tw