



Security—purpose Industrial PoE Switch

Specially designed for HD IP camera data and PoE access


Industrial-Level Chip Superior Performance

Adopt industrial MARVELL chip solution, backplane bandwidth up to 70Gbps, convenient for data processing of surveillance system.

Hybrid Fiber and Ethernet Gigabit uplink

Gigabit hybrid fiber and Ethernet uplink ports design, SFP fiber port, convenient for remote transmission of system; Ethernet port, convenient for local monitoring and data backup.





PoE+ 150m Downlink Ports

Provide 24x100Mbps 150m PoE+ downlink ports, meet needs of multi-channel PoE IP cameras; Support IEEE802.3 af/at standard, Max. 30W power, meet needs of high power cameras; Support IEEE802.3X full-duplex flow control and Auto MDI/MDIX function.



6KV Lightning protection Level 3 ESD

6KV lightning protection standard, level 3 ESD to ensure a stable and reliable operation environment.







L2 Management

It features the L2 management function, including a range of brilliant items: VLAN settings, QoS management, link management, port security, flow statistics, RSTP, rate limiting port mirroring, remote checking, camera reset, PoE output setup, MAC address binding, 802.1x certificates, IGMP Snooping, changeable Login account and IP Address setting, Logging Management, Mac table search, Email Notification, remote software upgrade and factory default settings.

H.		System sta	tus Port setting PoE VLAN GoS LA	CP Port security Netw	ork managemen	t Network statistics Sy		ement E	
L BRIDG.	Port settings	Port setting							
LIGHT SEED LIST	Port setting								
The state of the s	Port enable		Enable 💌						
	Portrate		Auto negotiation 💌 Dupi	lex mode Auto negotiation	~				
1/1	Flow control		Enable 💌						
	Portrange		OK.	Refresh					
ARREDD SOME				Current status		Port status	Port status		
HIIIII						Port rate(speediduplex)			
		1	pof1	no link	Copper	100884uto	enable	enat	
		2	po#2	no link	Copper	Auto/Auto	enable	disa	
I II ASSECTED A		3	port3	no link	Copper	AutolAuto	enable	das.	
THE PERSON NAMED IN		4	po#4	no link	Copper	AutolAuto	enable	ena	
The state of the s	NA D	6	po#5	no link	Copper	AutolAuto	enable	enal	