



APPLICATION



SPECIFICATION

| SOFTWARE | |
|--------------------------|---|
| Network Specification | IEEE802.3 10BaseT Ethernet IEEE802.3u 100BaseTX Fast Ethernet IEEE802.11n/b/g |
| Wireless | IEEE802.11n 8 ESSID |
| Frequency Band | 2.4 GHz frequency band |
| Wireless Operation Range | Up to 100 meters (outdoor) |
| Concurrent Devices | To extend wireless coverage, support Micro-USB to Ethernet for up to 50 devices |
| Wireless Data Rate | Up to 300Mbps with auto fall back with 802.11b/g |
| Networking | IP Plug and Play (iPnP) HTTP Proxy support SMTP server redirection DHCP server (RFC 2131) / DHCP relay (RFC 1542) Static IP / DHCP / PPPoE / PPTP WAN client NAT (RFC 1631); IP routing; NTP support Local account: 256 Max session number up to 16384 |
| Encryption | WEP 64/128bit, WPA-PSK TKIP, WPA2-PSK (AES) WPA/WPA2 Mix mode |
| Authentication | Built in authentication Radius authentication/ Accounting Web-based authentication/ Account manager/ Authorization user agreement |
| Billing | Accounting without PC operating Credit card support Free trail setting support 10 Customizable billing profile Prepaid billing mechanism Time-base billing/ Volume-base billing Account log max. 1000 |
| Security and Firewall | Layer 2 Isolation SSL Login Page/ SSL Administration VPN pass through (IPSec/PPTP/L2TP) Customize SSL certificate Pass through destination IP/URL Pass through source IP/MAC Restricted destination filtering IP/URL VPN PPTP client |
| Management | Remote web-based configuration and management Authorized remote management (Access Control List) Firmware upgrade (RFC 1350) via HTTP/TF TP Scheduled firmware upgrade Dynamic DNS Real-time current user list / DHCP clients list / Session list / Account list |

| Management | Secure Mail log function Syslog Bandwidth / Session control per user Session trace Secure remote SNMP V1/V2c (Read Only and OID 500) Ping command SSL certificate upload Internet access limit during the peak time* |
|--------------------------|--|
| Marketing Cooperation | Advertisement URL link Walled garden Customize login page, Logo, Information windows, Account print out, Credit card, User agreement Portal page QR code scan for login |
| HARDWARE | |
| Power Requirement | External power adaptor Input: 100-240 VAC, 50/60 Hz Output: 12V, 1.5Amp |
| Input / Output | One RJ-45 connector 10/100BaseTX WAN/WLAN Ethernet port with auto cross-over One Micro USB Connector Reset button Led Indicators |
| Dimension | (L): 109 mm / (W): 155 mm / (H): 90 mm Weight: about 340g (net) |
| Printer Tray | Push button: Push to open printer cover Tear bar: Cuts receipt paper Button A: Flashing when printer cover is opened Paper roll housing: Put paper roll here |
| Paper Roll Specification | (W): 58(+1/-1) mm / (L): 50meters (max) / Thickness: 65um Outside diameter: 63(+2/-2) mm Inside diameter: 12(+0.5/-0.5) mm Weight: 120 grams. |
| Environmental Conditions | Operating temperature: 0 °C to 50°C Storage temperature: -10 °C to 60°C Humidity: 10% ~ 90% non-condensing |
| Certification | FCC/ CE/ C-Tick/ VCCI/ GOST-R/ Telec/ NCC/ NTC/ FAC BSMI/ Anatel*/ COFETEL* |

* Features will be available in future release.



XENTINO TECHNOLOGIES CORP.

Tel : +886 2 8076 3071

Fax : +886 2 8076 3061

Website : www.xentino.com

E-mail : info@xentino.com

6F., No.93, Zhongcheng Rd., Tucheng Dist., New Taipei City 23674, Taiwan (R.O.C)

Copyright © 2014-2017 Xentino Technologies Corp. All Rights Reserved.

