

Standard Dome Camera

Features

- Sony Super HAD CCD sensor
- Built-in Board Lens
- 3-Axis Mechanism for free lens rotation
- DC or DC/AC Dual Voltage



Model No.	Mini	RYK-2311	RYK-2385	RYK-3341	RYK-3343
	Medium	RYK-2411	RYK-2485	RYK-3441	RYK-3443
	Medium(Space)	RYK-2G49	RYK-2G85	RYK-3G41	RYK-3G43
	Vandal proof(Mini)	RYK-2J49	RYK-2J85	RYK-3J41	RYK-3J43
	Vandal proof(Medium)	RYK-2H49	RYK-2H85	RYK-3H41	RYK-3H43
Image Device	1/3" Color Sony Super HAD		1/3" Color Sony Super HAD (Hi-Res.)		1/3" B/W Sony Super HAD (Hi-Res.)
Picture Elements	NTSC:510x492, PAL:500x582		NTSC:768x494, PAL:752x582		EIA:510x492, CCIR:500x582
Resolution	380 TVL		470 TVL		600 TVL
Min. Illumination	0.2 Lux / F2.0		0.3 Lux / F2.0		0.1 Lux / F2.0
S/N Ratio	More than 48dB				
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000			EIA:1/60~1/100,000, CCIR:1/50~1/110,000	
Gamma	0.45				
Lens Furnished	Board Lens 3.6mm / F2.0 (option:2.5/4.3/6/8/12)				
White Balance	Auto			-	
Gain Control	Auto				
Sync. System	Internal				
Video Output	1 Vp-p / 75 Ohms				
Audio Output	2 Vp-p / 50 Ohms (option, for RYK-x3xx series)				
Power Supply	DC12V±10%, Dual(for RYK-xHxx type only)				
Power Consumption	117mA max.	110mA max.	100mA max.	108mA max.	
Operating Temp.	-10°C ~ 50°C				