Vigor560

Wireless 11g CardBus Adapter

- Standards Compliance IEEE802.11gl,EEE802.11b
- Transmission Rate 54 Mbps



32-bit CardBus Type II



Vigor560 WLAN CardBus Adapter

■ CardBus

■ LED	Status		
Antenna	Internal printed antenna		
RADIO CHARACTERISTICS	DIO CHARACTERISTICS		
Standard	IEEE 802.11b and IEEE 802.11g		
Frequency Bands	2.412~ 2.497GHz ISM Band		
	802.11b: 11Mbps and 5.5Mbps CCK; 2Mbps: DQPSK;		
Modulation Tech	1Mbps: DBPSK		
	802.11g: OFDM		
Media Access Protocol	CSMA/CA with ACK		
Transmit Power	16.5 dBm @ Nominal Temp Range		
■ Data Rates	802.11b: 11Mbps, 5.5Mbps, 2Mbps, 1Mbps, auto fallback		
- Data Nates	802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps		
ENVIRONMENTAL			
Temperature	0°C to 60°C(Operating),-20°C to 80°C(Storing)		
Humidity	95% Non-condensing		
Power Consumption	Consumption Tx peak 470mA @ 3.3VDC, Rx peak 330mA @ 3.3VDC		
DRIVERS & UTILITY			
Operating Systems	Windows 98SE/2000/ME/XP		
Security	64/128 Bit WEP Key; WPA supports TKIP		
CERTIFICATION	WARRANTY		
FCC class B; CE Mark	■ One year limited		

PACKAGE CONTENTS

One Wireless LAN CardBus Adapter	One Setup CD-ROM with User Guide.
One Quick Installation Guide	

The Vigor560 is designed for the WLAN 2.4Ghz network throughout the EC region and Switzerland, with restriction in France!