Vigor600

Super G Wireless Adapter

- Standard Compliance 802.11b/g
- USB 2.0 interface



- High speed wireless connection
- Super G and eXtended Range (XR™) technology
- Industrial-strength WPA2 encryption
- Flexible cable for easy height and angle positioning
- Innovative design focus on simplicity and functionality

The Vigor600 Super G Wireless Adapter is a convenient wireless connectivity solution for desktop or notebook PCs. The Vigor600 can enable 802.11g wireless connectivity by simply utilizing your desktop or notebook PC's USB port without stringing Ethernet cables to your PC.

It can deliver unparalleled performance and industry-wide compatibility. With a maximum wireless signal rate of up to 108Mbps*, Vigor600 can transfer large files or view streaming video quickly and easily.

The Vigor600 Super G Wireless Adapter includes an intuitive configuration utility that allows you to discover and connect to other wireless networks in neighboring regions. Besides, such utility is able to create detailed connectivity profiles for the networks that you frequently access. Moreover, you can also enable support of WPA2 & 802.1x for enhanced data encryption and user authentication.

With the advantages in short size and sturdy speed, Vigor600 Super G Wireless Adapter is suitable for travel. It is a convenient solution for providing high performance wireless connectivity to your desktop or notebook PC.





Best with Vigor2800G Super G ADSL2/2+ Security Router



Vigor600

Super G Wireless Adapter

Specifications

Operation Mode	Infrastructure & Ad-hoc mode
RF Spread Scheme	802.11g: OFDM
	802.11b: Direct Sequence Spread Spectrum (DSSS)
	[CCK,BPSK,QPSK]
Frequency Band	2.4GHz
Transmission Rate	802.11g Super G mode: 108Mbps*
	802.11g: 54, 48, 36, 24, 18, 12, 9, and 6Mbps
	802.11b: 11, 5.5, 2, and 1Mbps
Channels Support (RF Frequency Range)	US/Canada: 11 channels (1 ~ 11)
	Japan: 14 channels (1 ~ 13) or 1 (14th)
	Europe: 13 channels (1 ~ 13)
	France: 4 channels (10 ~ 13)
Security	64/128/256-bit WEP encryption, WPA2, 802.1x authentication
Radio Power	15 dBm at 11g mode, 17 dBm at 11b mode
Operation Distance **	Indoor: 50 meter
	Outdoor: 300 meter
Antenna Type	A ceramic chip antenna
Interface Type	USB 2.0
Receiver Sensitivity	Max: -89 dBm
Operating Environment	Operating temperature: 0 ~ 55 °C
	Storage temperature: -25 ~ 80 °C
Operation Voltage	5.0 Volts±10%
Operation Voltage Power Consumption	5.0 Volts±10% Max: 500mA
	_
Power Consumption	Max: 500mA
Power Consumption	Max: 500mA US: FCC part 15
Power Consumption Regulatory Approval	Max: 500mA US: FCC part 15 Europe: EN 300 328, EN301489-17, EN60950
Power Consumption Regulatory Approval Dimensions	Max: 500mA US: FCC part 15 Europe: EN 300 328, EN301489-17, EN60950 96 mm (L) *30 mm (W) *11.7 mm (H)
Power Consumption Regulatory Approval Dimensions	Max: 500mA US: FCC part 15 Europe: EN 300 328, EN301489-17, EN60950 96 mm (L) *30 mm (W) *11.7 mm (H) Installation CD with user's guide and utility

The Vigor600 is designed for the WLAN 2.4GHz network throughout the EC region and Switzerland, with restriction in France.

* Actual data throughput will vary according to the network conditions and environmental factors, including volume of network traffic network overhead and building materials.

** Environment conditions may adversely affect wireless operation distance.

