

Release Note for VigorAP 912C

Firmware Version:	1.4.0
Release Type:	Normal
Applied Models:	VigorAP 912C

VigorAP 912C is a ceiling-mount Wi-Fi for business networks. It has a capacity of up to 256 concurrent active users, ideal for a high-density environment such as a BYOD workplace. The low-profile appearance and PoE power supply provide the flexibility in deployment.

New Features

- Support Hotspot Web Portal (LAN>>Hotspot Web Portal).
- Support new authentication mechanism for MyVigor server.
- Support to manage other VigorAP devices (Central AP Management >> General Setup).

Improvement

- Improved: Add Last Sync update time information in Mesh >> Mesh Setup page.
- Improved: Add an option to enable / disable the WMM Capable setting on Wireless LAN >> Advanced Setting.
- Improved: Modify the default Mesh Preferred Uplink timeout options for mesh nodes. (Mesh>>Mesh Setup).
- Improved: Close TCP port 9608 when it is not used (e.g., not in Mesh Root mode and Root AP disabled) to improve security.
- Corrected: An issue of registration to MyVigor server.
- Corrected: An issue of image modification on quick start wizard.
- Corrected: An issue that mail alert did not work for smtp.gmail.com with port 587 and 25.
- Corrected: A display issue related to External Devices list with wrong HTTP port number.
- Corrected: An issue that the client was unable to connect to 2.4GHz after several days if Roaming was enabled.

Known Issue

- None.